



U.S. Department
of Transportation

East Building, PHH – 32
1200 New Jersey Avenue, Southeast
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

**The US Department of Transportation
Competent Authority for the United States**

CLASSIFICATION OF EXPLOSIVES

Based upon a request by ETA S.A., Roque Saenz Pena N 4029, Prov. de Buenos Aires, Argentina the following items are classed in accordance with Section 173.56, Title 49, Code of Federal Regulations (49 CFR). A copy of your application, all supporting documentation and a copy of this approval must be retained and made available to DOT upon request.

An EX approval is non-transferable in any merger, acquisition, sale of assets, or other business transaction. For more information, please visit:

[<https://phmsa.dot.gov/hazmat/energetic-material-legalchanges-faq>]

U.N. PROPER SHIPPING NAME AND NUMBER:

Cord, detonating, flexible, UN0289

U.N. CLASSIFICATION CODE: 1.4D

REFERENCE NUMBER

EX2017040308

PRODUCT DESIGNATION/PART NUMBER

ETA CORD: 80 RDX LS XHV, 80 HMX LS XHV,
60 RDX LS XHV, 60 HMX LS XHV, 40 RDX LS
XHV, 40 HMX LS XHV

NOTES: The classification is only valid when the cord is packaged as follows:
Inner Packaging - Trays, not less than 30mm thick polystyrene foam.
Outer Packaging - UN 4G fiberboard box with upper and lower fiberboard pads, each containing no more than thirty (30) inner packaging trays in up to 15 layers of 2 each and with a maximum of 500 feet of cord per outer packaging. The detonating cord is arranged in a serpentine arrangement of continuous loops throughout the inner packaging trays, with protective wire mesh sheathing and wooden spacer blocks placed to shield adjacent cord at all crossing points.

DATED: 08/09/2017

For William Schoonover
Associate Administrator for Hazardous Materials Safety

