



## TECHNICAL DATA SHEET

### Description:

OILWELL FLEXIBLE JACKET DETONATING CORD  
80g/ft 17g/m HMX – Low Shrink – Extra High Velocity

### Denomination:

**ETACORD 80 HMX LS XHV**

### Compounds

Explosive:	HMX	Color white/light grey
Textil:	Aramide Fiber	Color yellow
Jacket:	POLIAMYDE	Color brillant green

### Characteristics

Temperature Resistance:	204°C / 1h
Shrinkage:	2 % 185°C
Velocity of Detonation:	8000 m/s
Lap Joint Sensitivity:	Yes*
Outside Diameter:	5.3 mm ± 0,2 mm

Note: Not recommended for exposed use.

### Packaging

UN Risk Clasification:	1.4 D
UN Number:	0289
Quantityper box:	152.4 m (500 ft)
Gross Wt:	16.1 kg
Net Wt:	4.6 kg
NEC per box:	2.59 kg

Also available airshipable packing.

ETASA (ARGENTINA) S.A.

Ruta 25 Km 13 (Esq. Salta) Villa Rosa – Pilar – Bs. As.

Tel: +54 230 4494382/167/311 Fax: +54 230 4494165

[www.etasa.com](http://www.etasa.com)

\*100% for 50mm overlapped detonating cord to detonating cord.  
Side initiation depends on detonator output