



TECHNICAL DATA SHEET

Description:

OILWELL FLEXIBLE JACKET DETONATING CORD
80g/ft-17g/m RDX – Low Shrink – Extra High Velocity

Denomination:

ETACORD 80 RDX LS XHV

Compounds

Explosive:	RDX	Color white/light grey
Textil:	Aramide Fiber	Color yellow
Jacket:	POLIAMYDE	Color brillant black

Characteristics

Temperature Resistance:	160°C / 1h
Shrincage:	2 % 160°C
Velocity of Detonation:	7500 m/s
Lap Joint Sensitivity:	Yes*
Outside Diameter:	5.3 mm ± 0,2 mm
Note: Not recommended for exposed use.	

Packaging

UN Risk Clasification:	1.4 D	
UN Number:	0289	
Quantityper box:	152.4	Mts. (500 Ft.)
Gross Wt:	16.1	Kg.
Net Wt:	4.6	Kg.
NEC per box:	2.59	Kg.

ETASA (ARGENTINA) S.A.
Ruta 25 Km 13 (Esq. Salta) Villa Rosa – Pilar – Bs. As.
Tel: +54 230 4494382/167/311Fax: +54 230 4494165
www.etasa.com

*100% for 50mm overlapped detonating cord to detonating cord.
Side initiation depends on detonator output