



TECHNICAL DATA SHEET

Description:

OILWELL FLEXIBLE JACKET DETONATING CORD
80g/ft-17g/m HMX – Low Shrink – Extra High Velocity

Denomination:

ETACORD 80 HMX LS XHV

Compounds

Explosive:	HMX	Color white/light grey
Textil:	Aramide Fiber	Color yellow
Jacket:	POLIAMYDE	Color brillant green

Characteristics

Temperature Resistance:	204°C / 1h
Shrinkage:	1 % 185°C
Velocity of Detonation:	8000 m/s
Lap Joint Sensitivity:	Yes*
Outside Diameter:	5.3 mm ± 0,2 mm
Note: Not recommended for exposed use.	

Packaging

UN Risk Clasification:	1.1 D
UN Number:	0065
Quantityper box:	152.4 m (500 ft)
Gross Wt:	6.2 kg
Net Wt:	4.3 kg
NEC per box:	2.59 kg

Also available airshipable packing.

ETASA (ARGENTINA) S.A.
Ruta 25 Km 13 (Esq. Salta) Villa Rosa – Pilar – Bs. As.
Tel: +54 230 4494382/167/311 Fax: +54 230 4494165
www.etasa.com

*100% for 50mm overlapped detonating cord to detonating cord.
Side initiation depends on detonator output